



Admonter FLOORs on underfloor heating systems

Admonter FLOORs are ideally suited for underfloor heating systems. We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors, they have to be fully glued down). We recommend hot-water underfloor heating systems set at low temperature. Please find detailed information in the information sheet Admonter FLOORs on underfloor heating systems!

Admonter room concepts

Our floors, walls, ceilings, stairs, doors or even acoustic solutions are perfectly harmonised to turn your ideas into reality and give every room a very special atmosphere.

Regular care and maintenance

Please see the Admonter maintenance & installation instructions or visit admonter.com/de/downloads/

Please note: Easy-Care (EC) natural oiled easy care - NO INITIAL OIL TREATMENT REQUIRED! For repair and supplementary oils see the Admonter pricelist.

Please note: Pro Care Plus (PC+): All Pro Care Plus Floors are hardened by oxidation & additionally actory-maintained. NO initial maintenance required.

| Grading | Thickness (mm) | Construction | Width (mm) | Format | Length (mm) | Texture | Finish | Profile |
|---------|----------------|--------------|------------|---------|-------------|----------------------------|--------|-----------------|
| basic | 15 | 3-layer | 195 | classic | 1850 | brushed | ec | Tongue & groove |
| | | | 195 | classic | 2000 | brushed | ec | Tongue & groove |
| | | | 195 | classic | 2400 | brushed | ec | Tongue & groove |
| | | | 195 | classic | 1850 | brushed | ec | lock-it |
| | | | 195 | classic | 2000 | brushed | ec | lock-it |
| | | | 195 | classic | 2400 | brushed | ec | lock-it |
| | | | 158 | xxlong | 3870 | brushed | ec | Tongue & groove |
| | | | 158 | xxlong | 4470 | brushed | ec | Tongue & groove |
| | | | 158 | xxlong | 4870 | brushed | ec | Tongue & groove |
| | | | 192 | xxlong | 3870 | brushed | ec | Tongue & groove |
| | | | 192 | xxlong | 4470 | brushed | ec | Tongue & groove |
| | | | 192 | xxlong | 4870 | brushed | ec | Tongue & groove |
| | | | 195 | classic | 1850 | strongly brushed | pc+ | Tongue & groove |
| | | | 195 | classic | 2000 | strongly brushed | pc+ | Tongue & groove |
| | | | 195 | classic | 2400 | strongly brushed | pc+ | Tongue & groove |
| | | | 195 | classic | 1850 | strongly brushed | pc+ | lock-it |
| | | | 195 | classic | 2000 | strongly brushed | pc+ | lock-it |
| | | | 195 | classic | 2400 | strongly brushed | pc+ | lock-it |
| | | | 158 | xxlong | 3870 | strongly brushed | pc+ | Tongue & groove |
| | | | 158 | xxlong | 4470 | strongly brushed | pc+ | Tongue & groove |
| | | | 158 | xxlong | 4870 | strongly brushed | pc+ | Tongue & groove |
| | | | 192 | xxlong | 3870 | strongly brushed | pc+ | Tongue & groove |
| | | | 192 | xxlong | 4470 | strongly brushed | pc+ | Tongue & groove |
| | | | 192 | xxlong | 4870 | strongly brushed | pc+ | Tongue & groove |
| | | | 195 | classic | 1850 | autentico strongly brushed | pc+ | Tongue & groove |
| | | | 195 | classic | 2000 | autentico strongly brushed | pc+ | Tongue & groove |
| | | | 195 | classic | 2400 | autentico strongly brushed | pc+ | Tongue & groove |

ec: natural oiled easy care
pc+: natural oiled pro care+

Technical information

More information (for example concerning fire classification) in the accompanying information to CE-marking at <http://www.admonter.eu/de/downloads/>


| Type of wood | Width (mm) | Weight [kg/m ²] | Moisture content [%] | Lambda [W/m K] | D-Value R [m ² K/W] | Hardness [N/mm ²] | Fire classification |
|--------------|------------|-----------------------------|----------------------|----------------|--------------------------------|-------------------------------|---------------------|
| Spruce | 15 | 7 | 8+/-2 | 0,12 | 0,125 | 12 | F _{fl} * |





*Full surface glueing & Factory finish C_{fl}-s1





| Feature wooden floors | Benefit |
|--|---|
| Choice of countless wood species, in particular reclaimed wood | Wide range of options for customized products, precisely tailored to customer benefits / requirements -> for every customer or area of application. |
| Different structure possibilities and colour shades | |
| Individual colours (Easy-Color) | The right surface for every customer or area of application / living situation Oberflächenvergleich Flüssigkeitstest |
| Different surfaces (natural oiled easy-care, natural-oiled pro-care, matt lacquered) – advantages EC | |
| Different construction variants, thicknesses and profiles / installation systems | The right product for every application / purpose |
| Different formats (SMALL, CLASSIC, LONG, XXLlong) | The right product for every room size and situation |
| Different widths that can be laid together | Great appearance of the floor in large rooms |
| Admonter solid wood construction for 3-layer floors (top layer, perpendicular middle layer, backside as a counter layer with solid wood construction) For wood type oak 240mm width = hardwood reverse side | Rigid against torsion -> the floor lies flatter and the position of joints is reduced, even with wide plank flooring |

| | |
|----------------------------------|---|
| ADMONTER ACCESSORIES SKIRTING | Type 2 D  |
|----------------------------------|---|

| | | | | |
|--------------------------------------|---|---|---|---|
| ADMONTER ACCESSORIES STAIR NOSING | Example pictures! All available stair nosings (depending on wood type and thickness), you can find in the price list. | | Example object | |
| |  |  |  |  |