Admonter & Heritage Collection













Top layer aprox. 3,6 mm Maintenance oil easy care white



Admonter FLOORs on underfloor heating systems

Admonter FLOORs are ideally suited

for underfloor heating systems. We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors, they have to be fully glued down). We recommend hot-water underfloor heating systems set at low temperature. Please find detailed information in the information sheet Admonter FLOORs on underfloor heating systems!



Our floors, walls, ceilings, stairs, doors or even acoustic solutions are perfectly harmonised to turn your ideas into reality and give every room a very special atmosphere.

Regular care and maintenance

Please see the Admonter maintenance & installation instructions or visit admonter.com/de/downloads/

Please note: Easy-Care (EC) natural oiled easy care - NO INITIAL OIL TREATMENT REQUIRED! For repair and supplementary oils see the Admonter pricelist.

Grading	Thickness (mm)	Construction	Width (mm)	Format	Length (mm)	Texture	Finish	Profile
	15	3-layer	161	classic	1850	brushed	ec	Tongue & groove
naturelle			161	classic	2000	brushed	ec	Tongue & groove
			161	classic	2400	brushed	ec	Tongue & groove
			161	classic	1850	brushed	ec	lock-it
			161	classic	2000	brushed	ec	lock-it
			161	classic	2400	brushed	ec	lock-it
			195	classic	1850	brushed	ec	Tongue & groove
			195	classic	2000	brushed	ec	Tongue & groove
			195	classic	2400	brushed	ec	Tongue & groove
			195	classic	1850	brushed	ec	lock-it
			195	classic	2000	brushed	ec	lock-it
			195	classic	2400	brushed	ec	lock-it
			240	classic	2000	brushed	ec	Tongue & groove
			240	classic	2400	brushed	ec	Tongue & groove
			240	xxlong	3870	brushed	ec	Tongue & groove
			240	xxlong	4470	brushed	ec	Tongue & groove
			240	xxlong	4870	brushed	ec	Tongue & groove

ec: natural oiled easy care

Room concepts

made of natura wood for floors, walls & ceilings

More information (for example concerning fire classification) in the accompanying information to CE-marking at http://www.admonter.eu/de/downloads/									
Type of wood	Width (mm)	Weight [kg/m2 []]	Moisture content [%]	Lambda [W/m K]	D-Value R [m² K/W]	Hardness [N/mm²]	Fire classification		
Larch	15	7,8	8+/-2	0,14	0,107	20	C _{ff} -s1		





Top layer aprox. 3,6 mm Maintenance oil easy care white

Wooden floors Floors

admonter.com

















Feature wooden floors	Benefit		
Choice of countless wood species, in particular reclaimed wood	Wide range of options for customized products, precisely tailored		
Different structure possibilities and colour shades	to customer benefits / requirements -> for every customer or area of application.		
Individual colours (Easy-Color)	The right surface for every customer or area of application / living		
Different surfaces (natural oiled easy-care, natural-oiled pro-care, matt lacquered) – advantages EC	situation Oberflächenvergleich Flüssigkeitstest		
Different construction variants, thicknesses and profiles / installation systems	The right product for every application / purpose		
Different formats (SMALL, CLASSIC, LONG, XXLong)	The right product for every room size and situation		
Different widths that can be laid together	Great appearence of the floor in large rooms		
Admonter solid wood construction for 3-layer floors (top layer, perpendicular middle layer, backside as a counter layer with solid wood construction)	Rigid against torsion -> the floor lies flatter and the positon of joints is reduced even with wide plant flooring		



For wood type oak 240mm width = hardwood reverse side

		ctures! All available s	Example object				
ADMONTER ACCESSORIES STAIR NOSING	-	-)	->	-	->	T	1

joints is reduced, even with wide plank flooring

Wooden floors **Floors**

Wooden panels Elements

Wooden acoustic panels

Wooden stairs

Wooden doors