## **OAK SETA**





### Admonter FLOORs on underfloor heating systems

Admonter FLOORs are ideally suited for underfloor heating systems. We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors and 3-layer floors small, they have to be fully glued down). We recommend hot-water underfloor heating systems set at low temperature. Please find detailed information in the information sheet Admonter FLOORs on underfloor heating systems!

### Admonter accessories

The wide range of accessories matches the Admonter FLOORs and includes flush-mount skirting and solutions for staircases.

#### Regular care and maintenance

Please see the Admonter maintenance & installation instructions or visit www.admonter.eu/en/downloads/.

PLEASE NOTE: natural oiled easy care - NO INITIAL OIL TREATMENT IS REQUIRED! Repair and supplementary oils you can find in our Admonter price list. Further information about our products can be found at admonter.at

Grading	Thickness (mm)	Construction	Width (mm)		Length (mm)	Texture	Finish	Profile
basic	10	2-layer	158	classic	2000	brushed	ec	lock-it
			180	classic	2000	brushed	ec	lock-it
		3-layer	158	classic	1850 / 2000 / 2400	brushed	ec	Tongue & groove
	15					brushed	ec	lock-it
						cross	ec	Tongue & groove
			192	classic	1850 / 2000 / 2400	brushed	ec	Tongue & groove
						brushed	ec	lock-it
						cross	ec	Tongue & groove
rustic	10	2-layer	158	classic	2000	brushed	ec	lock-it
			180	classic	2000	brushed	ec	lock-it
	15	3-layer	158	classic	1850 / 2000 / 2400	brushed	ec	Tongue & groove
						brushed	ec	lock-it
						cross	ec	Tongue & groove
			192	classic	1850 / 2000 / 2400	brushed	ec	Tongue & groove
						brushed	ec	lock-it
						cross	ec	Tongue & groove
						used	ec	lock-it/ Tongue & groove

Backing: Solid wood / ec: natural oiled easy care / pc: natural oiled pro care / ml: matt lacquer

Please note: this product gets lighter during the first time after installation!

Technical information  More information (for example concerning fire classification) in the accompanying information to CE-marking at http://www.admonter.eu/en/downloads/											
Type of wood	Thickness (mm)	Weight [kg/m²]	Moisture content [%]	Lambda [W/m K]	D-Value R[m² K/W]	Hardness [N/mm²]	Fire classification				
Oak	10	5,7	7+/-2	0,15	0,067	41	C <sub>ff</sub> -s1				
Oak LH-RS	15	8,6	7+/-2	0,15	0,100	41	C <sub>ff</sub> -s1				
Oak NH-RS	15	7,8	7+/-2	0,14	0,107	41	C <sub>ff</sub> -s1				

LH-RS: Hardwood-Backing / NH-RS: Softwood-Backing



















## SMOKED PRODUCTS



### Smoked products:

The smoking process naturally highlights the color differences caused by fluctuations in the tannic acid content of the tree. Due to the change in pH during the smoking process, these tannins react with the atmospheric oxygen, which causes the desired color changes. Since the pH value does not suddenly change at the end of the smoking process and atmospheric oxygen is also omnipresent, natural post-ripening processes occur. These ripening processes subside in the first few months until the desired color is achieved.

This play of colors can be seen on a small scale within a plank and over a large area from one plank to another.

### Natural colour changes:

All Admonter floors are a natural product and will over time change colour. Depending on the amount of exposure your floor has to sunlight, lighter timber will turn darker and darker timber will become lighter. This change is most pronounced in the first 3-6 months.

















# SMOKED PRODUCTS



























# SMOKED PRODUCTS























