

Top layer 2-/3-layer approx. 3,6mm brown filler Maintenance oil white







Admonter FLOORs on underfloor heating systems

Like all Admonter FLOORs the Multibond is suitable for use over underfloor heating systems. 2-layer is installed fully bonded. 3-layer can be installed floating. However,

we recommend to install fully bonded using Admonter elastic adhesive. We recommend hot-water underfloor heating systems set at low temperature. Please find more information in the PDF Underfloor-heating systems.

Admonter accessories

The wide range of accessories matches the Admonter FLOORs and includes flushmount skirting and solutions for staircases.

Regular care and maintenance

Please see the Admonter maintenance & installation at https://admonter.com/en/downloads/

PLEASE NOTE: natural oiled easy care - NO INITIAL OIL TREATMENT REQUIRED! For repair and supplementary oils see the Admonter pricelist.

The illustrations are a guide to the appearance of the grading. Admonter flooring is a 100 % natural product. A picture never replaces the reallity. For this reason we recommend a visit to your nearest Admonter flooring dealer. He will be pleased to show you samples.

Bevel	Thickn. approx. (mm)	TL-Thickn. approx. (mm)	Construction	Width approx. (mm)		approx. im)	Texture	Finish	Profile
with bevel	10	3,6	2-layer	130	small	1200	brushed	ec	Tongue & groove
				130	small	1200	sanded	ml	Tongue & groove
without bevel	10	3,6	2-layer	130	small	1200	sanded	ml	Tongue & groove
with bevel	15	3,6	3-layer	195	classic	2400	brushed	ec	Tongue & groove
				195	classic	2400	sanded	ml	Tongue & groove
				195	classic	2400	brushed	ec	lock-it
				195	classic	2400	sanded	ml	lock-it

ec: natural oiled easy care, ml: matt lacquered

BENEFITs at a glance - a technical comparison							
Dimension	The large dimension (up to 2400 x 195 mm) with the special small rods optics saves time during installtion.						
	2 constructions (2-/3-layer)						
	2 thicknesses and profiles: approx. 10 mm, 2-layer, tongue & groove - for fully-glue-down installation approx. 15 mm, 3-layer, tongue & groove or lock-it - for floating and fully-glue-down installation						
Design	The various lengths of the rods contribute to a design highlight - rod length up to 1000 mm						
Weight	A big advantage is the low weight, even having bigger packaging.						
Highlights	Small rod optics - for the first time available in Larch.						
	Improved warp stability due to 2- and 3-layer solid wood construction.						

Installation	2-layer	3-layer			
floating	no	yes			
stick down	Admonter elastic adhesive notched trowel B11 expansion joints <u>installation instructions</u>	Admonter elastic adhesive notched trowel B11 expansion joints installation instructions			

Technical Data For details (e.g. fire effects) please see CE-marking at https://admonter.com/en/downloads/								
Type of wood	Construction	Thickn. (mm)	Weight [kg/m²]	Moisture content [%]	Lambda [W/m K]	D-Value R [m² K/W]	Hardness [N/mm²]	Fire classification
Oak	2-layer	10	5,7	7+/-2	0,15	0,067	41	C _f -s1
	3-layer	15	7,8	7+/-2	0,14	0,113	41	C _f -s1

Admonter flooring is a 100 % natural product. A picture never replaces the reallity. For this reason we recommend a visit to your nearest Admonter flooring dealer. He will be pleased to show you samples.

FPD (1977) Series admonter.com

Wooden Panels

Elements

Wooden Acoustic Panels

Acoustics

Wooden Stairs

Stairs

Wooden Doors

Doors

Admonter Holzindustrie AG Sägestraße 539 | 8911 Admont, Austria +43 (0) 3613 3350 | info@admonter.at

FN237499p Landesgericht Leoben, Gerichtsstand Liezen | UID-Nr.: ATU57198366 May 2022 Raiffeisenbank Admont, IBAN: AT88 3800 1000 0002 7276 | BIC: RZSTAT213001 Errors and omissions excepted.



brown filler Maintenance oil white





Wooden Floors Floors














Floors

Wooden Floors





Admonter flooring is a 100 % natural product. A picture never replaces the reallity. For this reason we recommend a visit to your nearest Admonter flooring dealer. He will be pleased to show you samples.


Wooden Stairs **Stairs**

The illustrations are a guide to the appearance of the grading.

Wooden Doors Doors

Admonter Holzindustrie AG Sägestraße 539 | 8911 Admont, Austria +43 (0) 3613 3350 | info@admonter.at

FN237499p Landesgericht Leoben, Gerichtsstand Liezen | UID-Nr.: ATU57198366 May 2022 Raiffeisenbank Admont, IBAN: AT88 3800 1000 0002 7276 | BIC: RZSTAT213001 Errors and omissions excepted.





Top layer 2-/3-layer approx. 3,6mm brown filler Maintenance oil white






Wooden Floors Floors







Admonter flooring is a 100 % natural product. A picture never replaces the reallity. For this reason we recommend a visit to your nearest Admonter flooring dealer. He will be pleased to show you samples.

Wooden Floors

Floors

Elements

Wooden Panels

Wooden Acoustic Panels

Wooden Stairs

Stairs

Wooden Doors

Doors

Admonter Holzindustrie AG Sägestraße 539 | 8911 Admont, Austria

FN237499p Landesgericht Leoben, Gerichtsstand Liezen | UID-Nr.: ATU57198366 May 2022 Raiffeisenbank Admont, IBAN: AT88 3800 1000 0002 7276 | BIC: RZSTAT213001 Errors and omissions excepted.



brown filler Maintenance oil white



Room concepts made of natural WOOd for floors, walls & ceilings

Surface finishes in comparison: same colour but different appearance



matt lacquered natural oiled easy care



The illustrations are a guide to the appearance of the grading.



Admonter flooring is a 100 % natural product. A picture never replaces the reallity. For this reason we recommend a visit to your nearest Admonter flooring dealer. He will be pleased to show you samples



Wooden Floors Floors











Wooden Floors Floors

Wooden Panels Elements

Wooden Acoustic Panels Acoustics

Wooden Stairs **Stairs**

Wooden Doors Doors