



Admonter FLOORs on underfloor heating systems

Like all Admonter FLOORs the Multibond is suitable for use over underfloor heating systems. 2-layer are installed fully bonded. 3-layer can be installed floating. However, we recommend to install fully bonded using Admonter elastic adhesive. We recommend hot-water underfloor heating systems set at low temperature. Please find more information in the PDF Underfloor-heating systems.

Admonter accessories

The wide range of accessories matches the Admonter FLOORs and includes flush-mount skirting and solutions for staircases.

Regular care and maintenance

Please see the Admonter maintenance & installation at <https://admonter.com/en/downloads/>

PLEASE NOTE: natural oiled easy care - NO INITIAL OIL TREATMENT REQUIRED! For repair and supplementary oils see the Admonter pricelist.

The illustrations are a guide to the appearance of the grading. Admonter flooring is a 100 % natural product. A picture never replaces the reality. For this reason we recommend a visit to your nearest Admonter flooring dealer. He will be pleased to show you samples.

Bevel	Thickn. approx. (mm)	TL-Thickn. approx. (mm)	Construction	Width approx. (mm)	Length approx. (mm)	Texture	Finish	Profile	
with bevel	10	3,6	2-layer	130	small	1200	brushed	ec	Tongue & groove
				130	small	1200	sanded	ml	Tongue & groove
without bevel	10	3,6	2-layer	130	small	1200	sanded	ml	Tongue & groove
with bevel	15	3,6	3-layer	195	classic	2400	brushed	ec	Tongue & groove
				195	classic	2400	sanded	ml	Tongue & groove
				195	classic	2400	brushed	ec	lock-it
				195	classic	2400	sanded	ml	lock-it

ec: natural oiled easy care, ml: matt lacquered

BENEFITs at a glance - a technical comparison

Dimension	The large dimension (up to 2400 x 195 mm) with the special small rods optics saves time during installation.
	2 constructions (2-/3-layer)
	2 thicknesses and profiles: approx. 10 mm, 2-layer, tongue & groove - for fully-glue-down installation approx. 15 mm, 3-layer, tongue & groove or lock-it - for floating and fully-glue-down installation
Design	The various lengths of the rods contribute to a design highlight – rod length up to 1000 mm
Weight	A big advantage is the low weight, even having bigger packaging.
Highlights	Small rod optics - for the first time available in Larch.
	Improved warp stability due to 2- and 3-layer solid wood construction.

Installation	2-layer	3-layer
floating	no	yes
stick down	Admonter elastic adhesive notched trowel B11 expansion joints installation instructions	Admonter elastic adhesive notched trowel B11 expansion joints installation instructions

Technical Data

For details (e.g. fire effects) please see CE-marking at <https://admonter.com/en/downloads/>

Type of wood	Construction	Thickn. (mm)	Weight [kg/m²]	Moisture content [%]	Lambda [W/m K]	D-Value R [m² K/W]	Hardness [N/mm²]	Fire classification
Ash	2-layer	10	5,5	7+/-2	0,14	0,073	38	C _{fl} -s1
	3-layer	15	7,8	7+/-2	0,14	0,107	38	C _{fl} -s1

Admonter flooring is a 100 % natural product. A picture never replaces the reality. For this reason we recommend a visit to your nearest Admonter flooring dealer. He will be pleased to show you samples.



The illustrations are a guide to the appearance of the grading.

Admonter flooring is a 100 % natural product. A picture never replaces the reality. For this reason we recommend a visit to your nearest Admonter flooring dealer. He will be pleased to show you samples.



The illustrations are a guide to the appearance of the grading.

Admonter flooring is a 100 % natural product. A picture never replaces the reality. For this reason we recommend a visit to your nearest Admonter flooring dealer. He will be pleased to show you samples.