



brown filler

### Admonter FLOORs on underfloor heating systems

Like all Admonter FLOORs the Multibond is suitable for use over underfloor heating systems. 2-layer is installed fully bonded. 3-layer can be installed floating. However, we recommend to install fully bonded using Admonter elastic adhesive. We recommend hot-water underfloor heating systems set at low temperature. Please find more information in the PDF Underfloor-heating systems.

### Admonter accessories

The wide range of accessories matches the Admonter FLOORs and includes flush-mount skirting and solutions for staircases.

### Regular care and maintenance

Please see the Admonter maintenance & installation at <https://admonter.com/en/downloads/>

**PLEASE NOTE:** natural oiled easy care - NO INITIAL OIL TREATMENT REQUIRED! For repair and supplementary oils see the Admonter pricelist.

The illustrations are a guide to the appearance of the grading. Admonter flooring is a 100 % natural product. A picture never replaces the reality. For this reason we recommend a visit to your nearest Admonter flooring dealer. He will be pleased to show you samples.

Bevel	Thickn. approx. (mm)	TL-Thickn. approx. (mm)	Construction	Width approx. (mm)	Length approx. (mm)		Texture	Finish	Profile
with bevel	10	3,6	2-layer	130	small	1200	brushed	ec	Tongue & groove
with bevel	15	3,6	3-layer	195	classic	2400	brushed	ec	Tongue & groove
				195	classic	2400	brushed	ec	lock-it

ec: natural oiled easy care

### BENEFITS at a glance - a technical comparison

Dimension	The large dimension (up to 2400 x 195 mm) with the special small rods optics saves time during installation. 2 constructions (2-/3-layer)
Design	2 thicknesses and profiles: approx. 10 mm, 2-layer, tongue & groove - for fully-glue-down installation approx. 15 mm, 3-layer, tongue & groove or lock-it - for floating and fully-glue-down installation
Weight	The various lengths of the rods contribute to a design highlight – rod length up to 1000 mm
Weight	A big advantage is the low weight, even having bigger packaging.
Highlights	Small rod optics - for the first time available in Larch. Improved warp stability due to 2- and 3-layer solid wood construction.

Installation	2-layer	3-layer
floating	no	yes
stick down	Admonter elastic adhesive notched trowel B11 expansion joints <a href="#">installation instructions</a>	Admonter elastic adhesive notched trowel B11 expansion joints <a href="#">installation instructions</a>

### Technical Data

For details (e.g. fire effects) please see CE-marking at <https://admonter.com/en/downloads/>

Type of wood	Construction	Thickn. (mm)	Weight [kg/m²]	Moisture content [%]	Lambda [W/m K]	D-Value R [m² K/W]	Hardness [N/mm²]	Fire classification
Larch	2-layer	10	5,3	8+/-2	0,14	0,079	20	C <sub>e</sub> -s1
	3-layer	15	7,8	8+/-2	0,14	0,107	20	C <sub>e</sub> -s1

Admonter flooring is a 100 % natural product. A picture never replaces the reality. For this reason we recommend a visit to your nearest Admonter flooring dealer. He will be pleased to show you samples.





The illustrations are a guide to the appearance of the grading.

Admonter flooring is a 100 % natural product. A picture never replaces the reality. For this reason we recommend a visit to your nearest Admonter flooring dealer. He will be pleased to show you samples.