

Ash

filled with brown filler

Admonter

Wooden panels

A: Typical structural appearance of rift and plain cut, virtually knotless, occasional knot points possible, no brown heart, slight colour variations possible, jointfree gluing.

B: Typical structural appearance of rift and plain cut; sound knots possible, occasional dead knots, knotholes professionally filled, brown heart possible, natural colour variations, jointfree gluing.



The above picture shows an example of the natural character of the wood, this will vary in every panel.



Characteristics

Grading	Thickness mm app.	Length mm (Width 2030 mm)	Top layer thickness mm	Top layer width mm	Middle layer	Packaging pack./palett
A/B	19	2400	3,6	158	Ash	30
	19	2400	3,6	158	SML Softwood	30

Panels are glued SWP/2 NS (non structural): solid wood panels for non-structural use in wet areas, with regard to appropriate constructional protection also suitable for exterior use (sheltered areas). Legend: SML = strip core, BML = board middle layer. More information concerning fire classification in the accompanying information to CE-marking.

Technical information

More information (for example concerning fire classification) in the accompanying information to CE-marking at <http://www.admonter.com/de/downloads/>

Type of wood	Thickness (mm)	Middle layer	Weight [kg/m ²]	Moisture content [%]	Lambda [W/m K]
Ash	19	Ash	13,3	7+/-2	0,17
	19	Softwood	10,5	7+/-2	0,14



Errors and changes excepted.

Admonter Holzindustrie AG | Sägestraße 539 | 8911 Admont, Austria | info@admonter.at | admonter.com

4. 09. 2024



Feature Wooden Floors	Benefit
Choice of countless wood species, in particular reclaimed wood	Wide range of options for customized products, precisely tailored to customer benefits / requirements -> for every customer or area of application.
Different structure possibilities and colour shades	
Individual colours (Easy-Color)	The right surface for every customer or area of application / living situation
Different surfaces (natural oiled easy-care, natural-oiled pro-care, matt lacquered) - advantages EC	
Different construction variants, thickness and profiles / instalation systems	The right product for every application / purpose
Different formats (SMALL, CLASSIC, LONG, XXLlong)	The right product for every room size and situation
Different widths that can be laid together	Great appearance on the floor in large rooms
Admonter solid wood construction for 3-layer floors (top layer, perpendicular middle layer, backside as a counter layer with solid wood construction) For wood type oak 240mm width = hardwood reverse side	Rigid against torsion -> the floor lies flatter and the position of joints is reduced, even with wide plank flooring

