

Spruce AB/ST - Top layer

filled with brown fillers

Admonter

Wooden panels

Top layer AB: Varying colour and structure due to origin and wood. Resins, knots and splay knots; small boxwood, small heartwood, small black knots
Cracks, light blue and round knots with bark; Slats glued joint-tight except for sauna-suitable slats laid joint-tight.

Rückseite ST: Varying colour and structure due to origin and wood; resins, knots and splay knots; small boxwood, heartwood, black knots
Cracks, light blue and round knots with bark; filled knot holes, jointfree gluing of the lamellas

This board is also available with glue suitable for saunas and meets the formaldehyde emission requirements according to ÖNORM M 6219-1:2010.

Particularly when used in saunas, individual possible resin leaks and flaking should be taken into account. The maximum permissible temperature of 105°C must not be exceeded locally (e.g. near the oven). Where necessary, conformity with ÖNorm M 6219 or the relevant other national or local requirements must be ensured by the planning/executing company. Please also note our data sheet "[Use in saunas](#)"



The above picture shows an example of the natural character of the wood, this will vary in every panel.

Top layer

Grading	Thickness mm app.	Length mm (Width 2030 mm)	Top layer thickness mm	Top layer width mm	Middle layer	Packaging pack./palett
AB/ST	12	5000	3,6	146	BML Spruce	25
AB/ST (suitable for sauna use)	19	5000	6	146	BML Spruce	30
AB/ST	27	5000	9	146	BML Spruce	20

Panels are glued SWP/2 NS (non structural); solid wood panels for non-structural use in wet areas, with regard to appropriate constructional protection also suitable for exterior use (sheltered areas). Legend: SML = strip core, BML = board middle layer. More information concerning fire classification in the accompanying information to CE-marking.

Technical information

More information (for example concerning fire classification) in the accompanying information to CE-marking at <http://www.admonter.com/de/downloads/>

Type of wood	Thickness (mm)	Middle layer	Weight [kg/m ²]	Moisture content [%]	Lambda [W/m K]
Spruce	12	Spruce	5,6	8+/-2	0,12
	19	Spruce	8,9	8+/-2	0,12
	27	Spruce	12,7	8+/-2	0,12



Errors and changes excepted.

Admonter Holzindustrie AG | Sägestraße 539 | 8911 Admont, Austria | info@admonter.at | admonter.com

05.09.2024

Spruce AB/ST - Top layer

filled with brown fillers

Admonter

Wooden panels



Bottom layer



Errors and changes excepted.

Admonter Holzindustrie AG | Sägestraße 539 | 8911 Admont, Austria | info@admonter.at | admonter.com

05.09.2024

Spruce AB/ST - Top layer

filled with brown fillers

Admonter

Wooden panels



Spruce gehackt

Feature Wooden Floors	Benefit
Choice of countless wood species, in particular reclaimed wood	Wide range of options for customized products, precisely tailored to customer benefits / requirements -> for every customer or area of application.
Different structure possibilities and colour shades	
Individual colours (Easy-Color)	The right surface for every customer or area of application / living situation
Different surfaces (natural oiled easy-care, natural-oiled pro-care, matt lacquered) - advantages EC	
Different construction variants, thickness and profiles / installation systems	The right product for every application / purpose
Different formats (SMALL, CLASSIC, LONG, XXLong)	The right product for every room size and situation
Different widths that can be laid together	Great appearance on the floor in large rooms
Admonter solid wood construction for 3-layer floors (top layer, perpendicular middle layer, backside as a counter layer with solid wood construction) For wood type oak 240mm width = hardwood reverse side	Rigid against torsion -> the floor lies flatter and the position of joints is reduced, even with wide plank flooring

