

Larch

filled with brown filler

Admonter

Wooden panels

AB: Mostly sound knots, occasional black knots, knotholes are professionally filled, small filled knots, occasional pith ray, occasional resin pockets, no sapwood, slight compression wood and slight colour variations are possible, jointfree gluing.

Bottom layer standard: closed jointing, no blue-stain.



The above picture shows an example of the natural character of the wood, this will vary in every panel.

Top layer

Grading	Thickness mm app.	Length mm (Width 2030 mm)	Top layer thickness mm	Top layer width mm	Middle layer	Packaging pack./palett
AB/ST	19	4000-5000	5	114/120/137/146	SML or MML-Larch	30

Panels are glued SWP/2 NS (non structural): solid wood panels for non-structural use in wet areas, with regard to appropriate constructional protection also suitable for exterior use (sheltered areas). Legend: SML = strip core, BML = board middle layer. More information concerning fire classification in the accompanying information to CE-marking.

Technical information					
More information (for example concerning fire classification) in the accompanying information to CE-marking at http://www.admonter.com/de/downloads/					
Type of wood	Thickness (mm)	Middle layer	Weight [kg/m ²]	Moisture content [%]	Lambda [W/m K]
Larch	19	Larch	11,0	8+/-2	0,15



Errors and changes excepted.

Admonter Holzindustrie AG | Sägestraße 539 | 8911 Admont, Austria | info@admonter.at | admonter.com

5.09.2024



Feature Wooden Floors	Benefit
Choice of countless wood species, in particular reclaimed wood	Wide range of options for customized products, precisely tailored to customer benefits / requirements -> for every customer or area of application.
Different structure possibilities and colour shades	
Individual colours (Easy-Color)	
Different surfaces (natural oiled easy-care, natural-oiled pro-care, matt lacquered) - advantages EC	The right surface for every customer or area of application / living situation
Different construction variants, thickness and profiles / installation systems	The right product for every application / purpose
Different formats (SMALL, CLASSIC, LONG, XXLlong)	The right product for every room size and situation
Different widths that can be laid together	Great appearance on the floor in large rooms
Admonter solid wood construction for 3-layer floors (top layer, perpendicular middle layer, backside as a counter layer with solid wood construction) For wood type oak 240mm width = hardwood reverse side	Rigid against torsion -> the floor lies flatter and the position of joints is reduced, even with wide plank flooring

