Wooden doors


Oak Kimi (grey)

Top layer approx. 2,5 mm Maintenance oil grey



Wooden stairs





Admonter wooden floors are ideally suited for underfloor heating systems. We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors and 3-layer floors small, they have to be fully glued down). We recommend hot-water underfloor heating systems set at low temperature. Please find detailed information in the information sheet Admonter on underfloor heating systems.

Admonter accessories

The wide range of accessories matches your natural wooden floor and includes skirting boards and staircase solutions.

Regular care and maintenance

Please see the Admonter maintenance & installation instructions or visit http://www.admonter.com/en/downloads/

PLEASE NOTE: natural oiled easy care - NO INITIAL OIL TREATMENT IS REQUIRED! Repair and supplementary oils you can find in our Admonter price list. Further information about our products can be found at admonter.at

Admonter is a 100% natural product. A picture can therefore never reflect the original. We recommend a consultation based on sample boards.

Grading	Thickness (mm)	Construction	Width (mm)	Length (mm)		Texture	Finish	Profile
calm (elegance)	13	3-layer	192	classic	2400	brushed	ec	lock-it
placid (basic)	13	3-layer	158	classic	2000	brushed	ec	lock-it
			192	classic	2000 / 2400	brushed	ec	lock-it
vivid (rustic)	13	3-layer	158	classic	2000	brushed	ec	lock-it
			192	classic	2000 / 2400	brushed	ec	lock-it

Backing: Solid wood / ec: natural oiled easy care

Technical information							
More information (for example concerning fire classification) in the accompanying information to CE-marking a http://www.admonter.com/en/downloads							
Type of wood	Thickness (mm)	Weight [kg/m²]	Moisture content [%]	Lambda [W/m K]	D-Value R [m² K/W]	Hardness [N/mm²]	Fire classification
Oak	13	6,7	7+/-2	0,13	0,098	41	C _{ff} -s1























Wooden Floors Floors

Wooden stairs

Wooden doors

Oak Kimi (grey) Top layer approx. 2,5 mm Maintenance oil grey Room concepts made of natural wood for floors, it walls & ceilings



Feature wooden floors	Benefit		
Choice of countless wood species, in particular reclaimed wood	Wide range of options for customized products, precisely tailored to		
Different structure possibilities and colour shades	customer benefits / requirements -> for every customer or area of application.		
Individual colours (Easy-Color)	The right finish for every customer or area of application / living		
Different finishings (natural oiled easy-care / natural oiled pro care / matt lacquereded	situation Finish Video liquid test		
Different construction variants, thicknesses and profiles / installation systems	The right product for every application / purpose		
Different formats (SMALL, CLASSIC, LONG, XXLong)	The right product for every room size and situation		
Different widths that can be laid together	Great appearence of the floor in large rooms		
Admonter solid wood construction for 3-layer floors (top layer, perpendicular middle layer, backside as a counter layer with solid wood construction) For wood Typee oak 240mm width = hardwood reverse side	Rigid against torsion -> the floor lies flatter and the positon of joints is reduced, even with wide plank flooring		

ADMONTER ACCESSORIES SKIRTING BOARDS



ADMONTER ACCESSORIES STAIR NOSINGS























