Reclaimed wood oak

Admonter

black fillers

AHEI: Reclaimed wood oak with a surface full of character, contrasting colour variations are a valued feature, sound knots, black knots, spike knots acceptable, heartwood, partial rot, irregular wormholes, shakes, nail holes, material inclusions, bark pockets as well as mechanical damages acceptable. Lamellas are joint free placed but not joint free glued.

Bottom layer C: Oak, no special quality specifications, holes are not filled.



Grading	Thickness mm approx.	Length mm (Width 2030 mm)	Top layer thickn. mm approx.	Top layer width mm	Middle layer	Packaging pieces/palett
AHEI/C	19	2000-3500	4	Mix	SML-Softwood	30

The panels are SWP/2 non structural (NS) glued: solid wood panels for non-structural use in wet areas, with regard to appropriate constructional protection also suitable for exterior use (sheltered areas). Legend: SML = strip core, BML = board middle layer. More information concerning fire classification in the accompanying information to CE-marking.

Technical information More information (for example concerning fire classification) in the accompanying information to CE-marking at http://www.admonter.com/en/downloads/						
Type of wood	Thickness (mm)	Middle layer	Weight [kg/m²]	Moisture content [%]	Lambda [W/m K]	
Reclaimed wood oak	19	Spruce	10,4	7+/-2	0,14	

















Reclaimed wood oak

Admonter

black fillers



Features wooden panels Elements	Benefit		
Standard-width 2030 mm for ALL ELEMENTs	Simple stock-keeping (no short lengths: e.g. reclaimed wood) Calculation of offcuts / less articles by product group -> more comprehensive		
Choice of countless wood species – in particular reclaimed wood	- Wide range of options for customized products, tailored to customer benefits / requirements. The right surface for every customer and area of application / living situation.		
Different texture options and colours			
Also available for sauna use			
A wide range of construction variants	The right product for every application.		
Service programme – cutting to size and simple edge processing and milling work, as well as surface treatment and application of different textures	Capacity balancing in the event of overload of the processor's production / possibility to buy ready-to-assemble furniture parts		















