Top layer: Vibrant stick look in plain and veneered wood, healthy knots and black knots permitted, knots and splits are professionally repaired, growth-specific and wood type-specific differences in colour and structure are part of the appearance, joint-tight gluing.

Backing: as above



Grading	Thickness mm ca.	Length in mm (width 2030 mm)	Top layer thickness mm ca.	Top layer width	Middle layer	Packaging pieces/pallet
MB/MB	19	2400	3,6	Multibond	softwood	30
	29	2400	3,6	Multibond	softwood	20

The panels are SWP/2 non structural (NS) glued: solid wood panels for non-structural use in wet areas, with regard to appropriate constructional protection also suitable for exterior use (sheltered areas). Legend: SML = strip core, BML = board middle layer. More information concerning fire classification in the accompanying information to CE-marking.

Technical information								
More information (for example concerning fire classification) in the accompanying information to CE-marking at http://www.admonter.com/en/downloads/								
Type of wood	Thickness (mm)	Middle layer	Weight [kg/m²]	Moisture content [%]	Lambda [W/m K]			
Oak Multibond	19	softwood	10,4	7+/-2	0,14			
	29	spruce	15,2	7+/-2	0,14			



















Features wooden panels Elements	Benefit		
Standard width 2030mm for all natural wooden panels	Simple stock-keeping (no short lengths: e.g. reclaimed wood) Calculation of offcuts / less articles by product group -> more comprehensive		
Choice of countless wood species - in particular reclaimed wood	Wide range of options for customized products, tailored to customer		
Different texture options and colours	benefits / requirements. The right surface for every customer and area of application / living situation.		
Also available for sauna use	area or approaudity living situation.		
A wide range of construction variants	The right product for every application.		
Service programme – cutting to size and simple edge processing and milling work, as well as surface treatment and application of different textures	Capacity balancing in the event of overload of the processor's production / possibility to buy ready-to-assemble furniture parts		















