

# Oak medium Marrone

Top layer approx. 3,6 mm  
Maintenance oil brown  
thermo-treated

# Admonter

Wooden Floors



Grading: basic



## Admonter on underfloor heating systems

Admonter wooden floors are ideally suited for underfloor heating systems. We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors and 3-layer floors small, they have to be fully glued down). We recommend hot-water underfloor heating systems set at low temperature. Please find detailed information in the information sheet [Admonter on underfloor heating systems](#).

## Admonter accessories

The wide range of accessories matches your natural wooden floor and includes skirting boards and staircase solutions.

## Regular care and maintenance

Please see the Admonter maintenance & installation instructions or visit <http://www.admonter.com/en/downloads/>

**PLEASE NOTE:** natural oiled easy care - NO INITIAL OIL TREATMENT IS REQUIRED! You can find repair and supplementary oils in our Admonter price list.

Admonter is a 100% natural product. A picture can therefore never reflect the original. We recommend a consultation based on sample boards.

Grading	Thickness (mm)	Construction	Width (mm)	Format	Length (mm)	Texture	Finish	Profile
noblesse	15	3-layer	188	classic	2000	brushed	ec	Tongue & groove
basic	10	2-layer	120	small	1200	brushed	ec	Tongue & groove
	15	3-layer	188	classic	2000	brushed	ec	Tongue & groove
			188	classic	2000	antico	pc	Tongue & groove

## Technical information

More information (for example concerning fire classification) in the accompanying information to CE-marking a <http://www.admonter.com/en/downloads/>

Type of wood	Thickness (mm)	Weight [kg/m <sup>2</sup> ]	Moisture content [%]	Lambda [W/m K]	D-Value R [m <sup>2</sup> K/W]	Hardness [N/mm <sup>2</sup> ]	Fire classification
Oak medium Marrone	10	5,7	5+/-2	0,15	0,067	39	C <sub>e</sub> -s1
Oak medium Marrone	15	7,7	5+/-2	0,14	0,107	39	C <sub>e</sub> -s1



Errors and changes excepted.

Admonter Holzindustrie AG | Sägestraße 539 | 8911 Admont, Austria | [info@admonter.at](mailto:info@admonter.at) | [admonter.com](http://admonter.com)


15.04.2024

# Oak medium Marrone


Top layer approx. 3,6 mm  
 Maintenance oil brown  
 thermo-treated

# Admonter

Wooden Floors



Oak medium Marrone freshly installed



Oak medium Marrone mature

### Thermo-treated products:

To create these elegant, dark natural floors, European woods are darkened in a natural way – and this is done completely without pollutants and toxins using the proven heat-treatment process. This process allows the creation of various shades and nuances of colour. This enables us to create a large colour spectrum of dark woods in an environment-friendly way.

### Natural color changes:

All Admonter floors are a natural product and will over time change colour. Depending on the amount of exposure your floor has to sunlight, lighter timber will turn darker and darker timber will become lighter. This change is most pronounced in the first 3-6 months.

Feature wooden floors	Benefit
Choice of countless wood species, in particular reclaimed wood	Wide range of options for customized products, precisely tailored to customer benefits / requirements -> for every customer or area of application.
Different structure possibilities and colour shades	
Individual colours (Easy-Color)	The right finish for every customer or area of application / living situation <a href="#">Finish</a>   <a href="#">Video liquid test</a>
Different finishings (natural oiled easy-care / natural oiled pro care / matt lacquered) - advantages EC	
Different construction variants, thicknesses and profiles / installation systems	The right product for every application / purpose
Different formats (SMALL, CLASSIC, LONG, XXLlong)	The right product for every room size and situation
Different widths that can be laid together	Great appearance of the floor in large rooms
Admonter solid wood construction for 3-layer floors (top layer, perpendicular middle layer, backside as a counter layer with solid wood construction) For wood Type oak 240mm width = hardwood reverse side	Rigid against torsion -> the floor lies flatter and the position of joints is reduced, even with wide plank flooring

ADMONTER ACCESSORIES SKIRTING BOARDS	Type 1	Type 2 D

ADMONTER ACCESSORIES STAIR NOSINGS	Example pictures! All available stair nosings can be found in the price list	Example object

