

Oak

Top layer approx. 3,6 mm

Maintenance oil

Maintenance oil pro care

Admonter

Wooden Floors



Grading: basic



Admonter on underfloor heating systems

Admonter wooden floors are ideally suited for underfloor heating systems. We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors and 3-layer floors small, they have to be fully glued down). We recommend hot-water underfloor heating systems set at low temperature. Please find detailed information in the information sheet [Admonter on underfloor heating systems](#).

Admonter accessories

The wide range of accessories matches your natural wooden floor and includes skirting boards and staircase solutions.

Regular care and maintenance

Please see the Admonter maintenance & installation instructions or visit <http://www.admonter.com/en/downloads/>

PLEASE NOTE: natural oiled easy care - NO INITIAL OIL TREATMENT IS REQUIRED! You can find repair and supplementary oils in our Admonter price list.

Admonter is a 100% natural product. A picture can therefore never reflect the original. We recommend a consultation based on sample boards.

Grading	Thickness (mm)	Construction	Width (mm)	Format	Length (mm)	Texture	Finish	Profile
noblesse	10	2-layer	120	small	1200	brushed	ec	Tongue & groove
			158	small	1190	brushed	ec	Tongue & groove
	10,5	3-layer	158	classic	2000	brushed ¹⁾	ec	lock-it
			158	small	1190	brushed	ec	Tongue & groove
			158	classic	2000	brushed ¹⁾	ec	Tongue & groove
			158	classic	2000	brushed ¹⁾	ec	lock-it
			192	classic	2000	brushed ¹⁾	ec	Tongue & groove
			192	classic	2400	brushed ¹⁾	ec	Tongue & groove
			192	classic	2000	brushed ¹⁾	ec	lock-it
			192	classic	2400	brushed ¹⁾	ec	lock-it
elegance	10,5	2-layer	158	classic	2000	brushed ¹⁾	ec	lock-it
			158	classic	2000	brushed ¹⁾	ec	Tongue & groove
	15	3-layer	158	classic	2000	brushed ¹⁾	ec	lock-it
			192	classic	2000	brushed ¹⁾	ec	Tongue & groove
			192	classic	2400	brushed ¹⁾	ec	Tongue & groove
			192	classic	2000	brushed ¹⁾	ec	lock-it
			192	classic	2400	brushed ¹⁾	ec	lock-it
			192	classic	2000	brushed ¹⁾	ec	lock-it
			192	classic	2400	brushed ¹⁾	ec	lock-it
			192	classic	2400	brushed ¹⁾	ec	lock-it

¹⁾ also available with **sanded** texture - no item no.

Technical information

More information (for example concerning fire classification) in the accompanying information to CE-marking a <http://www.admonter.com/en/downloads/>

Type of wood	Thickness (mm)	Weight [kg/m ²]	Moisture content [%]	Lambda [W/m K]	D-Value R [m ² K/W]	Hardness [N/mm ²]	Fire classification
Oak	10	5,7	7+/-2	0,15	0,067	41	C ₂ -s1
Oak Hardwood-Backing	15	8,6	7+/-2	0,15	0,100	41	C ₂ -s1
Oak Softwood-Backing	15	7,8	7+/-2	0,14	0,107	41	C ₂ -s1



Errors and changes excepted.

Admonter Holzindustrie AG | Sägestraße 539 | 8911 Admont, Austria | info@admonter.at | admonter.com

18.06.2024

Oak

Top layer approx. 3,6 mm

Maintenance oil

Maintenance oil pro care

Admonter

Wooden Floors



Grading: basic



Admonter on underfloor heating systems

Admonter wooden floors are ideally suited for underfloor heating systems. We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors and 3-layer floors small, they have to be fully glued down). We recommend hot-water underfloor heating systems set at low temperature. Please find detailed information in the information sheet [Admonter on underfloor heating systems](#).

Admonter accessories

The wide range of accessories matches your natural wooden floor and includes skirting boards and staircase solutions.

Regular care and maintenance

Please see the Admonter maintenance & installation instructions or visit <http://www.admonter.com/en/downloads/>

PLEASE NOTE: natural oiled easy care - NO INITIAL OIL TREATMENT IS REQUIRED! You can find repair and supplementary oils in our Admonter price list.

Admonter is a 100% natural product. A picture can therefore never reflect the original. We recommend a consultation based on sample boards.

Grading	Thickness (mm)	Construction	Width (mm)	Format	Length (mm)	Texture	Finish	Profile
basic	10	2-layer	120	small	1200	brushed	ec	Tongue & groove
			158	small	1190	brushed	ec	Tongue & groove
			158	classic	2000	brushed ¹⁾	ec	lock-it
	15	3-layer	158	small	1190	brushed	ec	Tongue & groove
			158	classic	2000	brushed ¹⁾	ec	Tongue & groove
			158	classic	2000	scraped	ec	Tongue & groove
			158	classic	2000	antico	pc	Tongue & groove
			158	classic	2000	brushed ¹⁾	ec	lock-it
			192	classic	2000	brushed ¹⁾	ec	Tongue & groove
			192	classic	2400	brushed ¹⁾	ec	Tongue & groove
			192	classic	2000	scraped	ec	Tongue & groove
			192	classic	2400	scraped	ec	Tongue & groove
			192	classic	2000	antico	pc	Tongue & groove
			192	classic	2000	brushed ¹⁾	ec	lock-it
			192	classic	2400	brushed ¹⁾	ec	lock-it
			192	classic	2000	scraped	ec	lock-it
			192	classic	2400	scraped	ec	lock-it
			192	classic	2000	used	ec	Tongue & groove
			192	classic	2400	used	ec	Tongue & groove
			192	classic	2000	used	ec	lock-it
192	classic	2400	used	ec	lock-it			
naturelle	10,5	2-layer	158	classic	2000	brushed ¹⁾	ec	lock-it
			158	classic	2000	brushed ¹⁾	ec	Tongue & groove
	15	3-layer	192	classic	2000	brushed ¹⁾	ec	Tongue & groove
			192	classic	2400	brushed ¹⁾	ec	Tongue & groove
			192	classic	2000	brushed ¹⁾	ec	lock-it
			192	classic	2400	brushed ¹⁾	ec	lock-it
			240	classic	2400	brushed ¹⁾	ec	Tongue & groove
			240	classic	2400	scraped	ec	Tongue & groove
			280	long	2800	brushed ¹⁾	ec	Tongue & groove
			280	long	2800	scraped	ec	Tongue & groove

¹⁾ also available with **sanded** texture - no item no.



Oak

Top layer approx. 3,6 mm

Maintenance oil

Maintenance oil pro care

Admonter

Wooden Floors



Grading: basic



Admonter on underfloor heating systems

Admonter wooden floors are ideally suited for underfloor heating systems. We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors and 3-layer floors small, they have to be fully glued down). We recommend hot-water underfloor heating systems set at low temperature. Please find detailed information in the information sheet [Admonter on underfloor heating systems](#).

Admonter accessories

The wide range of accessories matches your natural wooden floor and includes skirting boards and staircase solutions.

Regular care and maintenance

Please see the Admonter maintenance & installation instructions or visit <http://www.admonter.com/en/downloads/>

PLEASE NOTE: natural oiled easy care - NO INITIAL OIL TREATMENT IS REQUIRED! You can find repair and supplementary oils in our Admonter price list.

Admonter is a 100% natural product. A picture can therefore never reflect the original. We recommend a consultation based on sample boards.

Grading	Thickness (mm)	Construction	Width (mm)	Format	Length (mm)	Texture	Finish	Profile
rustic	10,5	2-layer	158	classic	2000	brushed ¹⁾	ec	lock-it
			158	classic	2000	brushed ¹⁾	ec	Tongue & groove
			158	classic	2000	scraped	ec	Tongue & groove
			158	classic	2000	antico	pc	Tongue & groove
			158	classic	2000	brushed ¹⁾	ec	lock-it
			158	classic	2000	scraped	ec	lock-it
			192	classic	2000	brushed ¹⁾	ec	Tongue & groove
			192	classic	2400	brushed ¹⁾	ec	Tongue & groove
			192	classic	2000	scraped	ec	Tongue & groove
			192	classic	2400	scraped	ec	Tongue & groove
			192	classic	2000	antico	pc	Tongue & groove
			192	classic	2000	brushed ¹⁾	ec	lock-it
	15	3-layer	192	classic	2400	brushed ¹⁾	ec	lock-it
			192	classic	2000	scraped	ec	lock-it
			192	classic	2400	scraped	ec	lock-it
			158	classic	2000	autentico str. br.	pc	Tongue & groove
			192	classic	2000	autentico str. br.	pc	Tongue & groove
			192	classic	2400	autentico str. br.	pc	Tongue & groove
			192	classic	2000	used	ec	Tongue & groove
			192	classic	2400	used	ec	Tongue & groove
			192	classic	2000	used	ec	lock-it
			192	classic	2400	used	ec	lock-it
			240	classic	2400	brushed ¹⁾	ec	Tongue & groove
			240	classic	2400	scraped	ec	Tongue & groove
natur	15	3-layer	240 280/325	xxlong	4000 4500/5000	brushed ¹⁾	ec	Tongue & groove

¹⁾ also available with **sanded** texture - no item no.

Technical information

More information (for example concerning fire classification) in the accompanying information to CE-marking a <http://www.admonter.com/en/downloads/>

Type of wood	Thickness (mm)	Weight [kg/m ²]	Moisture content [%]	Lambda [W/m K]	D-Value R [m ² K/W]	Hardness [N/mm ²]	Fire classification
Oak	10	5,7	7+/-2	0,15	0,067	41	C ₂ -s1
Oak Hardwood-Backing	15	8,6	7+/-2	0,15	0,100	41	C ₂ -s1
Oak Softwood-Backing	15	7,8	7+/-2	0,14	0,107	41	C ₂ -s1



Errors and changes excepted.

Admonter Holzindustrie AG | Sägestraße 539 | 8911 Admont, Austria | info@admonter.at | admonter.com

18.06.2024

Oak

Top layer approx. 3,6 mm

Maintenance oil

Maintenance oil pro care

Admonter

Wooden Floors



Grading: basic

Feature wooden floors	Benefit
Choice of countless wood species, in particular reclaimed wood	Wide range of options for customized products, precisely tailored to customer benefits / requirements -> for every customer or area of application.
Different structure possibilities and colour shades	
Individual colours (Easy-Color)	The right finish for every customer or area of application / living situation Finish Video liquid test
Different finishings (natural oiled easy-care / natural oiled pro care / matt lacquered) - advantages EC	
Different construction variants, thicknesses and Profileees / installation systems	The right product for every application / purpose
Different formats (SMALL, CLASSIC, LONG, XXLlong)	The right product for every room size and situation
Different widths that can be laid together	Great appearance of the floor in large rooms
Admonter solid wood construction for 3-layer floors (top layer, perpendicular middle layer, backside as a counter layer with solid wood construction) For wood Type oak 240mm width = hardwood reverse side	Rigid against torsion -> the floor lies flatter and the position of joints is reduced, even with wide plank flooring

ADMONTER ACCESSORIES SKIRTING BOARDS	Type 1	Type 2 D	Type 3

ADMONTER ACCESSORIES STAIR NOSINGS	Example pictures! All available stair nosings can be found in the price list	Example object

