

# Pine white

Top layer approx. 3,6 mm  
Maintenance oil white

# Admonter

Wooden Floors



Grading: basic



## Admonter on underfloor heating systems

Admonter wooden floors are ideally suited for underfloor heating systems. We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors and 3-layer floors small, they have to be fully glued down). We recommend hot-water underfloor heating systems set at low temperature. Please find detailed information in the information sheet [Admonter on underfloor heating systems](#).

## Admonter accessories

The wide range of accessories matches your natural wooden floor and includes skirting boards and staircase solutions.

## Regular care and maintenance

Please see the Admonter maintenance & installation instructions or visit <http://www.admonter.com/en/downloads/>

**PLEASE NOTE:** natural oiled easy care - NO INITIAL OIL TREATMENT IS REQUIRED! You can find repair and supplementary oils in our Admonter price list.

Admonter is a 100% natural product. A picture can therefore never reflect the original. We recommend a consultation based on sample boards.

Grading	Thickness (mm)	Construction	Width (mm)	Format	Length (mm)	Texture	Finish	Profile
basic	15	3-layer	161	classic	1850	sanded	ec	Tongue & groove
			161	classic	2000	sanded	ec	Tongue & groove
			161	classic	2400	sanded	ec	Tongue & groove
			161	classic	1850	sanded	ec	lock-it
			161	classic	2000	sanded	ec	lock-it
			161	classic	2400	sanded	ec	lock-it

## Technical information

More information (for example concerning fire classification) in the accompanying information to CE-marking a <http://www.admonter.com/en/downloads/>

Type of wood	Thickness (mm)	Weight [kg/m <sup>2</sup> ]	Moisture content [%]	Lambda [W/m K]	D-Value R [m <sup>2</sup> K/W]	Hardness [N/mm <sup>2</sup> ]	Fire classification
Pine	15	7,2	8+/-2	0,14	0,107	19	F <sub>1</sub>



# Pine white

Top layer approx. 3,6 mm  
Maintenance oil white


# Admonter

Wooden Floors



Image: Pine

Feature wooden floors	Benefit
Choice of countless wood species, in particular reclaimed wood	Wide range of options for customized products, precisely tailored to customer benefits / requirements -> for every customer or area of application.
Different structure possibilities and colour shades	
Individual colours (Easy-Color)	The right finish for every customer or area of application / living situation <a href="#">Finish</a>   <a href="#">Video liquid test</a>
Different finishings (natural oiled easy-care / natural oiled pro care / matt lacquered) - advantages EC	
Different construction variants, thicknesses and Profilees / installation systems	The right product for every application / purpose
Different formats (SMALL, CLASSIC, LONG, XXLlong)	The right product for every room size and situation
Different widths that can be laid together	Great appearance of the floor in large rooms
Admonter solid wood construction for 3-layer floors (top layer, perpendicular middle layer, backside as a counter layer with solid wood construction) For wood Type oak 240mm width = hardwood reverse side	Rigid against torsion -> the floor lies flatter and the position of joints is reduced, even with wide plank flooring

<b>ADMONTER ACCESSORIES SKIRTING BOARDS</b>	Type 2 D 
---	---

<b>ADMONTER ACCESSORIES STAIR NOSINGS</b>	Example pictures! All available stair nosings can be found in the price list	Example object
		

