

## **RECLAIMED WOOD SUNBAKED BROWN**

AHSB: Reclaimed wood panel of pine, fir and spruce (species mixed) with a surface full of character and colour variation; sound knots, black knots, knot holes and spike knots possible; pith ray, resin pockets, worm holes, shakes, sapwood, nail holes, bark pockets and mechanical damages possible; colour variations: brown (light to dark brown, little different colour variations possible) are a valued feature. Top layers are joint free placed but not joint less glued.

Bottom layer C: Spruce, no special quality specification, not filled. Surface: raw/untreated and not brushed or sanded -> the textured surface is caused by natural weathering of the wood. This panel is also available with a gluing adapted to wet areas (sauna) and is therefore in accordance with the emission requirements according to ONORM M6219-1:2010 for the use in sauna areas (see information "Admonter Element's in sauna areas" at http://admonter.at/en/downloads/).









Grading	Thickness mm app.	Length mm (Width 2030 mm)	Top layer thickness mm	Top layer width mm	Middle layer	Packaging pack./palett
AHS/C (suitable for sauna use)	22	1800 - 3900 (subject to availa- bility)	8-9	Mix	BML or SML-Spruce (subject to availa- bility)	25
Panels are glued SW constructional protect Legend: SML = strip More information cond	tion also suitable core, BML = boar erning fire classifi	for extérior use (shei d middle layer. cation in the accomp	tered areas).	CE-marking.		
Type of wood	Thickness (mm)	Middle layer	Weight [kg/m <sup>2</sup> ]	Moi	sture content [%]	Lambda [W/m K]
Reclaimed Wood sunbake	d 22	Spruce	10,3		7+/-2	0,12
	show the range of ore detailed informa	possible colours. tion at: <b>admonter.at</b>			<b>F</b> 🕑 🚿	

Errors and changes possible, Phone: +43(0)3613/3350-0, Fax: +43(0)3613/3350-119, info@admonter.at, admonter.at