

# GALLERIA - RECLAIMED WOOD EXTREME

Surface full of character, sound and black knots possible, resin pockets, shakes, nail holes, mechanical damages and bark pockets possible. Colour variations and worm holes are a valued feature. Lamellas are jointfree placed but not jointless glued. Longitudinal and transverse joints of top layers possible.

**Surface:** brushed – holes are mainly filled.

**Bottom layer:** softwood, without special quality specification.



The above picture shows an example of the natural character of the wood, this will vary in every panel.

Characteristics

Finish	Thickness mm app.	Width mm	Length mm	Top Layer thickness mm	Packaging pieces/package	Matching trim
untreated or natural oiled	19	244	1800/2100 2250	app. 5	5	18 x 50 mm

**up to 25 m<sup>2</sup> - length 2400 mm**  
**from 25 m<sup>2</sup> - Lengths are subject to availability**

**GALLERIA glued SWP/1 NS (non structural):** solid wood panels for non-structural interior use.  
There is no risk of moisture penetration.

- Grooved on all four sides
- False tongue is included
- Matching trim and metal fixing brackets please see Admonter price list

More information concerning fire classification in the accompanying information to CE-marking.

## Technical information

More information (for example concerning fire classification) in the accompanying information to CE-marking at <http://www.admonter.eu/en/downloads>

Type of wood	Thickness (mm)	Middle layer	Weight [kg/m <sup>2</sup> ]	Moisture content [%]	Lambda [W/m K]
Reclaimed Wood extreme	19	Spruce	8,9	8+/-2	0,12



You can find more detailed information at: [admonter.at](http://admonter.at)