

Maintenance oil nature



The rough character of these floors makes them unsuitable to walk barefoot on them. They compensate with their uniqueness and their very special charm between design and alpine tradition.



Admonter FLOORS are ideally suited for underfloor heating systems. We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation. We recommend hot-water underfloor heating systems set at low temperature. Please find detailed information in the information sheet Admonter FLOORS on underfloor heating systems!

The wide range of accessories matches the Admonter FLOORs and includes flush-mount skirting and solutions for staircases.

Please see the Admonter maintenance & installation instructions for soaped floors or visit www.admonter.eu/en/downloads/.

Please note: - natural oiled pro care floors require a post-installation oil before they can be used.

Further Information: www.admonter.at

Grading	Thickness (mm)	Construction	Width (mm)	Length (mm)	Texture	Finish	Profile	
rustic	15	3-Layer	173	classic	1850 / 2000 / 2400	brushed	pc	Tongue & groove

Backing: Solid wood / **ec:** natural oiled easy care / **pc:** natural oiled pro care / **ml:** matt lacquer

More information (for example concerning fire classification) in the accompanying information to CE-marking at <http://www.admonter.eu/en/downloads/>

Type of wood	Thickness (mm)	Weight [kg/m ²]	Moisture content [%]	Lambda [W/m K]	d-Value R [m ² K/W]	Hardness [N/mm ²]	Fire classification
Reclaimed W. Oak	15	8,5	8+/-2	0,15	0,100	41	C _s -s1

