

RHOMBUS OAK WHITE

Top layer approx. 3,6 mm
Initial oil treatment required!
Maintenance oil white



Symbolfoto

Admonter FLOORs on underfloor heating systems

Admonter FLOORs are ideally suited for underfloor heating systems. We recommend hot-water underfloor heating systems set at low temperature.



Please find detailed information in the information sheet Admonter FLOORs on underfloor heating systems!

Admonter accessories

The wide range of accessories matches the Admonter FLOORs and includes matching boarders, flush-mount skirting and solutions for staircases.

Regular care and maintenance

Please see the Admonter maintenance & installation instructions for small format floorboards.

Further information

<http://www.admonter.eu/en/downloads/>

Grading	Thickness (mm)	Construction	Width (mm)	Texture	Finish	Profile
noblesse	15	3-Layer	approx. 270 x 470	brushed	ec	grooved on all four sides with false tongue

Backing: Massive wood / ec: natural oiled easy care / ml: matt lacquer

Please note:

A fully glued down installation with Admonter elastic adhesive is absolutely required!
Only left or right elements per package unit!

Technical information

More information (for example concerning fire classification) in the accompanying information to CE-marking at <http://www.admonter.eu/en/downloads/>

Type of wood	Thickness (mm)	Weight [kg/m ²]	Moisture content [%]	Lambda [W/m K]	d-Value R [m ² K/W]	Hardness [N/mm ²]	Fire classification
Oak	15	8,6	7+/-2	0,15	0,100	41	C ₁ -s1

