

# TWIN OAK

Top layer approx. 3,6 mm

Maintenance oil natur



**FLOORs**



symbolic photo

### Admonter FLOORs on underfloor heating systems

Admonter FLOORs are ideally suited for underfloor heating systems. We recommend hot-water underfloor heating systems set at low temperature.



Please find detailed information in the information sheet Admonter FLOORs on underfloor heating systems!

### Admonter accessories

The wide range of accessories matches the Admonter FLOORs and includes matching boarders, flush-mount skirting and solutions for staircases.

### Regular care and maintenance

Please see the Admonter maintenance & installation instructions for small format floorboards.

### Further information

<http://www.admonter.com/en/downloads/>

Grading	Thickness (mm)	Construction	Width (mm)	Length (mm)	Texture	Finish	Profile	
noblesse	10	2-Layer	120	small	590	sanded / brushed	ec	Tongue & groove
	15	3-Layer	120	small	590	sanded / brushed	ec	Tongue & groove
basic	10	2-Layer	120	small	590	sanded / brushed	ec	Tongue & groove
	15	3-Layer	120	small	590	sanded / brushed	ec	Tongue & groove

Backing: Solid Wood / ec: natural oiled easy care / ml: matt lacquer

### Please note:

Repair and supplementary oils can be found in the Admonter price list.

### Technical information

More information (for example concerning fire classification) in the accompanying information to CE-marking at <http://www.admonter.com/en/downloads/>

Type of wood	Thickness (mm)	Weight [kg/m <sup>2</sup> ]	Moisture content [%]	Lambda [W/m K]	d-Value R [m <sup>2</sup> K/W]	Hardness [N/mm <sup>2</sup> ]	Fire classification
Oak	10	5,7	7+/-2	0,15	0,067	41	C <sub>e</sub> -s1
Oak	15	8,6	7+/-2	0,15	0,100	41	C <sub>e</sub> -s1



Admonter flooring is a 100 % natural product. A picture is never a substitute for the „real thing“. For this reason we recommend a visit to your nearest Admonter flooring dealer. He will be pleased to show you samples.